

TECHNICAL DATA SHEET FLORPROTEC FLOR-LOCK

BASE MATERIALS & FEATURES

Flor-Lock is injection moulded using compound that has excellent wear characteristics, chemical resistance, long term stability and stable electrical properties.

FLAME RETARDANT DETAILS

Fire Performance does not support combustion and achieves Class 1 spread of flame when tested to BS476: Part 7 /DIN 13501:2004 – Bfl-S1. Resistance to Hot Objects/Solder – Good.

APPLICATIONS

Long term floor protection for factories, passenger terminals, warehouses, schools, garages, retail outlets, sports facilities and exhibitions.

ADVANTAGES

- Extremely hard wearing
- Ideal for use with fork trucks and heavy loads
- Quick and simple to install
- Good anti-slip properties
- Good thermal and acoustic insulation and excellent resistance to impact and vibration.
- Protects the existing floor from damage
- Ideal for uneven, damp or contaminated substrates
- Low life cycle cost and simple to maintain
- Environmentally friendly – 100% recyclable & zero VOC emissions

PRODUCT DETAILS

Code	TYPE	COLOURS AVAILABLE
5MM	Butterfly joint	001 Dark Grey, 002 Mid Grey, 004 Black, 006 Blue 009 Dark Green, 010 Yellow, 008 Red
6MM	Hidden joint	001 Dark Grey, 002 Mid Grey, 004 Black, 006 Blue
7MM	Industrial T joint	001 Dark Grey, 002 Mid Grey, 004 Black, 005 French Blue, 006 Dark Blue, 008 Red, 009 Green, 010 Yellow

