

TECHNICAL DATA SHEET FLORPROTEC POLYTHENE RANGE

BASE MATERIALS & FEATURES

Damp proof membranes are manufactured from 100% recycled polythene. Suitable for use as a Type 'A' DPM as defined by BSEN 13967:2012. Available in three thicknesses. Suitable for use below concrete floors in accordance with clause II of CP102: 1973.

Multi Poly is a wide width polythene sheeting with a multitude of uses from sheeting out, screening, general covering etc.

Florprotec orange FR poly is a heavy duty FR polythene used for screening off areas, general purpose film or when flame retardant heavy gauge material is needed. Also used in the asbestos industry.

FLAME RETARDANT DETAILS

Loss Prevention Standard

All flame retardant grades are flame retardant to Loss Prevention Standard 1207

APPLICATIONS

ADVANTAGES

PRODUCT DETAILS

Door frame protection - FR

Code	Product	Size
DPM1	DPM black	4m x 25m x 300mu
DPM2	DPM black	4m x 25m x 250mu
DPM3	DPM black	4m x 12.5m x 500mu
DPM4	DPM blue	4m x 25m x 300mu
DPM5	DPM blue	4m x 25m x 250mu
DPM6	DPM blue	4m x 12.5m x 500mu
DPM tape 1	Double sided	50mm x 10m
DPM tape 2	Single sided	100mm x 33m

Multi Poly

Multipoly light	Light duty	4m x 25m
Multipoly	Medium duty	4m x 25m
Multipoly HD	Heavy Duty	4m x 25m
Multipoly XHD	Extra heavy duty	4m x 50m
Multipoly 1000	Extra extra heavy duty	4m x 50m
Multipoly FR	Flame retardant	4m x 50m

Florprotec orange FR Poly

Orange Polythene heavy	4m x 25m
Orange Polythene light	4m x 50m

