

## TECHNICAL DATA SHEET FLORPROTEC PYROLAY P274



### BASE MATERIAL & FEATURES

Pyrolay is manufactured from flame retardant, anti-slip polyethylene. The surface is heat treated and shallow embossed to increase structural strength and further enhance the grip surface.

### FLAME RETARDANT DETAILS

Loss Prevention Standard 1207

All flame retardant grades are flame retardant to

Loss Prevention Standard 1207 (LPS1207)

Large flame test to LPS1207 - pass

ISO 4589 – 2: 1996 FAR 25.853

BS 476 Part 12 Source C JAR 25.853

BS 2782 Part 1 140E

BAE Systems Fire Test – FAR/JAR 25.853 appendix F vertical flame test - pass

### Accreditations:

Lloyds Register of Shipping

International Maritime Organisation

Det Norske Veritas

### APPLICATIONS

Heavy duty floor protection. Interior fitouts, scaffold towers – mezzanine height, forklifts, scissor lifts. To protect floors, stairs, walls, apertures, windows and doors from general site activity.

### ADVANTAGES

Proven protective properties on major projects. Supplied in rolls 1.5 m wide for quick and easy installation and removal. Textured anti-slip surface for good site safety. Can be custom printed in multi-colour.

### PRODUCT DETAILS

Product Code	Width	Length	Weight	Colour
P274 Blue (Heavy)	1500mm	100m	42kg	Blue