

TECHNICAL DATA SHEET FLORPROTEC PYROLAY GREEN M21

BASE MATERIAL & FEATURES

Pyrolay is manufactured from flame retardant, anti-slip polyethylene. The surface is heat treated and shallow embossed to increase structural strength and further enhance the grip surface.

FLAME RETARDANT DETAILS

Loss Prevention Standard 1207

All flame retardant grades are flame retardant to

Loss Prevention Standard 1207 (LPS1207)

Large flame test to LPS1207 - pass

ISO 4589 – 2: 1996 FAR 25.853

BS 476 Part 12 Source C JAR 25.853

BS 2782 Part 1 140E

BAE Systems Fire Test – FAR/JAR 25.853 appendix F vertical flame test - pass

Accreditations:

Lloyds Register of Shipping

International Maritime Organisation

Det Norske Veritas

APPLICATIONS

Medium duty floor protection. Interior fitouts tyred scaffold towers – mezzanine height, forklifts, scissor lifts. To protect floors, stairs, walls, apertures, windows and doors from general site activity.

ADVANTAGES

Proven protective properties on major projects. Supplied in rolls 1.5m wide for quick and easy installation and removal.. Textured anti-slip surface for good site safety. Can be custom printed in multi-colour.

PRODUCT DETAILS

Product Code	Width	Length	Weight	Colour
M21 Green (Medium)	1500mm	100m	17kg	Green

