

TECHNICAL DATA SHEET FLORPROTEC PYROLAY M41

BASE MATERIAL & FEATURES

Pyrolay is manufactured from flame retardant, anti-slip polyethylene. The surface is heat treated and shallow embossed to increase structural strength and further enhance the grip surface.

FLAME RETARDANT DETAILS

Loss Prevention Standard 1207

All flame retardant grades are flame retardant to

Loss Prevention Standard 1207 (LPS1207)

Large flame test to LPS1207 - pass

ISO 4589 – 2: 1996 FAR 25.853

BS 476 Part 12 Source C JAR 25.853

BS 2782 Part 1 140E

LPCB Certificated

BAE Systems Fire Test – FAR/JAR 25.853 appendix F vertical flame test - pass

Accreditations:

Lloyds Register of Shipping

International Maritime Organisation

Det Norske Veritas

APPLICATIONS

Floor protection & general purpose covering. Foot traffic and general snagging. To protect floors, stairs, walls, apertures, windows and doors from general site activity.

ADVANTAGES

Proven protective properties on major projects. Supplied in rolls 1.5 m wide for quick and easy installation and removal. White colour reflects available light assisting on site visibility. Textured anti-slip surface for good site safety. Can be custom printed in multi-colour.

PRODUCT DETAILS

Product Code	Width	Length	Weight	Colour
M41 (Light)	1500mm	200m	17kg	White

