

TECHNICAL DATA SHEET FLORPROTEC TACBAC CLEAR

BASE MATERIAL & FEATURES

Tacbac Clear is manufactured from polyethylene and coated on one side with a water based adhesive. The product is inside wound and is manufactured at 50 microns. Available as flat film or with embossed anti-slip finish.

FLAME RETARDANT DETAILS

BSAU169 (ISO3795) – burning resistance requirements, flammability testing – pass.

APPLICATIONS

- Use on carpet only. (not for smooth surfaces).
- Apply to clean and dry carpets, free from dust and excessive loose fibres.
- Avoid stretching the film when applying
- Press Tacbac Clear firmly onto carpet using a weighted roller (Tacbac applicator)
- Allow time for sub floor vapours / adhesives to evaporate before applying Tacbac Clear (this refers to vapours from newly glued down carpets and underlay).
- Tacbac Clear can be used for periods up to 8 weeks, for longer remove and renew.

Caution

- Never place Tacbac Clear on a wet or damp carpet.
- Avoid trapping vapours.
- Tacbac carpet cover should not be used on deep pile domestic carpets, similar to saxony style products or any deep pile carpet.
- Applying to used carpets is a risk area, particularly on soiled , contaminated or poor condition carpets. Our guidelines and cautions are to assist the user in minimising their risk.
- Do not use on smooth finishes, for carpets only

ADVANTAGES

PRODUCT DETAILS

Product Code	Width	Length	Weight	Colour
T37	600mm	100m	4kg	Clear
T37/50m.	600mm.	50m.	2.2kg	Clear
T5308	800mm	100m	6kg	Clear
T59	100mm	100m	7kg	Clear
T41	1200mm	100m	8kg	Clear
T51	600mm	25m	1kg	Clear
Antislip 0.6	600mm	100m	4kg	Clear

