

TECHNICAL DATA SHEET FLORPROTEC TACBAC FR & TS63 CERTIFIRE

BASE MATERIAL & FEATURES

Tacbac is manufactured from a flame retardant polyethylene film, coated on one side with an acrylic solvent-based adhesive. The product is self wound (i.e. does not use release paper) and is manufactured in 65 micron thickness as standard.

FLAME RETARDANT DETAILS

Loss Prevention Standard

TacBac FR is tested to TS63 Certifire and TacBac TS63 is both tested and certified to TS63 Certifire.

BS 476 part 12 Heat source C pass. German Marine B2 test – pass

BS EN ISO11925-2 ignitability of building products subjected to direct impingement of flame – pass.

PREN2824, 2825 & 2826 burning behaviour, determination of smoke density and gas components in the smoke of materials under the influence of radiating heat and flames – pass.

BS EN ISO4586-2 determination of burning behaviour by oxygen index – pass.

ISO 4589-2 1996 (oxygen index >23%) pass.

EN13501-1 Classification of reaction to fire performance – Pass

International Maritime Organisation

Florprotec TacBac is tested to the IMO flame retardant standard.

IMO resolution MSC 307 (88):annex 1 Part 5 (SOLAS 1974)

TOXICITY ACCREDITATIONS

Pr EN 2825 (smoke emission) <150 pass.

Pr EN 2826 (toxic gas emission) Pass (analytical report available on request).

APPLICATIONS

- Use on carpet only (not for smooth surfaces).
- Apply to clean and dry carpets, free from dust and excessive loose fibres.
- Avoid stretching the film when applying. Reverse wound – sticky side out to assist).
- Press TacBac FR firmly onto carpet using a weighted roller or glider.
- Allow time for vapours to evaporate before applying TacBac (this refers to vapours from newly glued down carpets and underlay).
- TacBac can be used for periods up to 8 weeks, for longer remove and renew.

Caution

- Never place TacBac FR on a wet or damp carpet.
- Avoid trapping vapours.
- Applying to used carpets is a risk area, particularly on soiled, contaminated or poor condition carpets. Our guidelines and cautions are to assist the user in minimising their risk.

PRODUCT DETAILS

Product Code	Width	Length	Weight	Colour
T57	600mm	100m	5.4kg	White
T54	1000mm	100m	9.0kg	White
T58	1200mm	100m	10.8kg	White
Tacbac TS63 CERTIFIRE				
T100FR	600mm	100m	5.4kg	White
T101FR	1000mm	100m	9.0kg	White
T102FR	1200mm	100m	10.8kg	White

Tacbac Dispensers

600mm Dispenser	0.6m
1000mm Dispenser	1.0m
1200mm Dispenser	1.2m

