

## TECHNICAL DATA SHEET FLORPROTEC TACBAC SMOOTH FR

### BASE MATERIAL & FEATURES

Tacbac is manufactured from a flame retardant polyethylene film, coated on one side with an acrylic solvent-based adhesive. The product is self wound (i.e. does not use release paper) and is manufactured in 70 micron thickness as standard.

### FLAME RETARDANT DETAILS

#### Loss Prevention Standard

TacBac Smooth FR is tested to TS63 Certifire

BS 476 part 12 Heat source C pass. German Marine B2 test – pass

BS EN ISO11925-2 ignitability of building products subjected to direct impingement of flame – pass.

PREN2824, 2825 & 2826 burning behaviour, determination of smoke density and gas components in the smoke of materials under the influence of radiating heat and flames – pass.

BS EN ISO4586-2 determination of burning behaviour by oxygen index – pass.

ISO 4589-2 1996 (oxygen index >23%) pass.

EN13501-1 Classification of reaction to fire performance – Pass

#### International Maritime Organisation

Florprotec TacBac is tested to the IMO flame retardant standard.

IMO resolution MSC 307 (88):annex 1 Part 5 (SOLAS 1974)

### TOXICITY ACCREDITATIONS

Pr EN 2825 (smoke emission) <150 pass.

Pr EN 2826 (toxic gas emission) Pass (analytical report available on request).

### APPLICATIONS

Used for protecting worktops, laminate floors and smooth floors from paint, scuff and scratches. It is quick and easy to apply and will peel clean after use.

### PRODUCT DETAILS

Product Code	Width	Length
SMOOTH FR	600mm	100m

